

EOLO AIR CONTROL



AIR

EN Tyre pressure control system

Eolo is a tyre inflator for cars and for small commercial vehicles – ideal for service stations, garages, car-body repairers and car dealers. Equipped with display and keypad for setting desired pressure; inflates and deflates. Works automatically and beeps when pressure reaches pre-set level.

Features

Max inflation pressure 5 bar (73 psi, 500 kPa)
Operating temperature -10/+50 °C
User-defined units of measurement (psi, kPa, bar)
Adjustable pressure sensor

Construction

Free-standing metal enclosure
10 metre air hose

Valve for connecting to tyres
Electronic panel with keypad and display
Air filters at intake and outlet
Built-in pressure regulator
Built-in overpressure safety valve

Optional

Compressor:
max delivery rate 6 m³/h
noise level <60 dB
motor capacity 1 kW



Automatic Start and Stop

Fully automatic

Stand Type



Panel Type




1

bar 2.2



Set pressure
Selezionare la pressione
Sélectionner la pression
Gewünschten Reifendruck einstellen
Planter la pression

2



Connect tyre
Connecter au pneu
Füllschlauch mit Reifen verbinden
Collegare la valvola al pneumatico
Conectar al neumático

3

Auto - STOP



Compressor



EOLO

Code	Description		Max inflating pressure			Compressor	Weight kg	Packaging mm
			bar	psi	kPa			
F00860000	Eolo tyre inflator Stand type w/compressor	AIR	5	73	500	●	50	1485x500x420
F00860010	Eolo tyre inflator Stand type w/o compressor	AIR	5	73	500	-	38	1485x500x420
F00860P00	Eolo tyre inflator Panel type	AIR	5	73	500	-	15	500x350x300