

accessories - grease fittings

## button heads

|          |   |
|----------|---|
| GBH1419B | Button head grease fitting 1/4" x 19 BSPF (10 pack) |
| GBH1828B | Button head grease fitting 1/8" x 28 BSPF (10 pack) |



GNP80M

## grease nipples

|               |  |
|---------------|--|
| GN061M90      | Grease nipple M6 x 1 90° angle (10 pack)         |
| GN061MST      | Grease nipple M6 x 1 straight (10 pack)          |
| GN081M90      | Grease nipple M8 x 1 90° angle (10 pack)         |
| GN081MST      | Grease nipple M8x 1 straight (10 pack)           |
| GN101M90      | Grease nipple M10 x 1 90° angle (10 pack)        |
| GN101MST      | Grease nipple M10 x 1 straight (10 pack)         |
| GN1428S45     | Grease nipple 1/4" 28 SAE LT 45° angle (10 pack) |
| GN1428S90     | Grease nipple 1/4" 28 SAE LT 90° angle (10 pack) |
| GN1428SST     | Grease nipple 1/4" 28 SAE LT straight (10 pack)  |
| GN1827N45     | Grease nipple 1/8" 27 NPT 45° angle (10 pack)    |
| GN1827N90     | Grease nipple 1/8" 27 NPT 90° angle (10 pack)    |
| GN1827NST     | Grease nipple 1/8" 27 NPT straight (10 pack)     |
| GNP80M GNP80S | Grease nipple assortment pack 80 piece metric    |
|               | Grease nipple assortment pack 80 piece SAE/NPT   |



GNP80s

## easy out tool

|      |                            |
|------|----------------------------|
| GNEL | Easy out tool - large GNES |
| GNES | Easy out tool - small      |



GNEs

## refillable bearing lubricators

|                 |
|-----------------|
| MCGL100 (100mL) |
| MCGL220 (220mL) |

These refillable automatic bearing lubricators are designed to provide constant lubrication to bearings, bushings, joints, articulated joints or wherever constant greasing is required. The lubricators are supplied with a setting dial which allows fixed dispensing of grease.

### Features & Benefits

- manufactured from transparent Lexan®
- setting dial (1, 3, 6 and 12 months)
- supplied with 2 springs, yellow (medium tension) black (strong tension)

MCGL100



MCGL220



accessories

## greasing couplers

### KY coupler

Standard supergrip coupler supplied with all Macnaught grease guns. Designed to fit most grease nipples and grease guns. Can be purchased separately or in packets of 8 (KY-8). Threads 1/8" BSP



### KDN right angle needlepoint coupler

Ideal where access to the grease nipple is minimal.



### KDR right angle coupler

For use in spaces when the area above the nipple is limited.



### KDS right angle coupler

A slightly shorter version of the KDR. Along with the KDN and KDR, it can be used with a flexible extension.



### KSR standard buttonhead coupler

For use on plant and machinery fitted with 5/8" buttonhead nipples. Length 72 mm (2 3/4").



### KGR giant buttonhead coupler

For use on plant and machinery fitted with 7/8" buttonhead nipples. Length 85 mm (3 3/8").



### KRV pressure release valve

Helps to prevent nipples from breaking off and couplers from splitting. Recommended for use with the K7 MINILUBE®, P3 POWERLUBE®, and P6 and P8 MAXILUBE®.



### KZD needlenose coupler

Used when nipples are recessed and standard couplers would meet with interference from surrounding components (universal joints, etc). Length 93 mm (3 3/4").



### KZDXL straight needlepoint coupler

Ideal for greasing the bearings on four wheel drive vehicles. Length 120 mm (4 3/4").



### KZE concave nipple coupler

Used when vehicles are fitted with special nipples or, in some cases, when normal nipples are damaged. Length 60 mm (2 1/4").



accessories

## greasing couplers

### KZX concave nipple coupler

A similar coupler to the KZE but fitted with a rigid extension. Length 200 mm (8").



### KN grease injector needle

Small needle used to inject sealed bearings and small lubrication points with grease when no grease nipples are present. Length 64 mm (2 1/2").



### KZHY hyperdermic needlepoint coupler

Ideal for use on bearings fitted with rubber dust covers. Length 130 mm (5 1/8").



### KZLN45 needlepoint coupler

Push on needle point grease extension with 45° angle at the end. Ideal for use with aircrafts. Length 300 mm (12")



### KZLNJ needlepoint coupler

Push on needlepoint extension with j bend at the end. Ideal for use with aircrafts. Length 300 mm (12")



### KZLNR needlepoint coupler

Push on needlepoint extension with 90° angle at the end. Ideal for use with aircrafts. Length 300 mm (12").



### KZLNS needlepoint coupler

Push on needlepoint grease extension, ideal for use with four wheel drive vehicles. Length 300 mm (12")



### KZSNR 90° needlepoint coupler

An 110 mm (4 1/4") needlepoint coupler with a 90° bend at the end.



### ZSB swivel

A 360° swivel supplied either separately or with the B2 Booster Gun. Threads 1/8" NPT (M) x 1/4" NPT (F).



## grease extension hoses

### KDE8 extension

A 200 mm (8") push on rigid extension coupler with a nipple to fit onto the KY coupler. For use with grease guns.



### KFR rigid/flexible extension

A 330 mm (13") extension with a sliding sleeve that allows for either flexible or rigid operation. The thread is 1/8" BSP (M) and fitted with a KY coupler.



accessories

## greasing couplers

### KY coupler

Standard supergrip coupler supplied with all Macnaught grease guns. Designed to fit most grease nipples and grease guns. Can be purchased separately or in packets of 8 (KY-8). Threads 1/8" BSP



### KDN right angle needlepoint coupler

Ideal where access to the grease nipple is minimal.



### KDR right angle coupler

For use in spaces when the area above the nipple is limited.



### KDS right angle coupler

A slightly shorter version of the KDR. Along with the KDN and KDR, it can be used with a flexible extension.



### KSR standard buttonhead coupler

For use on plant and machinery fitted with 5/8" buttonhead nipples. Length 72 mm (2 3/4").



### KGR giant buttonhead coupler

For use on plant and machinery fitted with 7/8" buttonhead nipples. Length 85 mm (3 3/8").



### KRV pressure release valve

Helps to prevent nipples from breaking off and couplers from splitting. Recommended for use with the K7 MINILUBE®, P3 POWERLUBE®, and P6 and P8 MAXILUBE®.



### KZD needlenose coupler

Used when nipples are recessed and standard couplers would meet with interference from surrounding components (universal joints, etc). Length 93 mm (3 3/4").



### KZDXL straight needlepoint coupler

Ideal for greasing the bearings on four wheel drive vehicles. Length 120 mm (4 3/4").



### KZE concave nipple coupler

Used when vehicles are fitted with special nipples or, in some cases, when normal nipples are damaged. Length 60 mm (2 1/4").



accessories

## greasing couplers

### KZX concave nipple coupler

A similar coupler to the KZE but fitted with a rigid extension. Length 200 mm (8").



### KN grease injector needle

Small needle used to inject sealed bearings and small lubrication points with grease when no grease nipples are present. Length 64 mm (2 1/2").



### KZHY hyperdermic needlepoint coupler

Ideal for use on bearings fitted with rubber dust covers. Length 130 mm (5 1/8").



### KZLN45 needlepoint coupler

Push on needle point grease extension with 45° angle at the end. Ideal for use with aircrafts. Length 300 mm (12")



### KZLNJ needlepoint coupler

Push on needlepoint extension with j bend at the end. Ideal for use with aircrafts. Length 300 mm (12")



### KZLNR needlepoint coupler

Push on needlepoint extension with 90° angle at the end. Ideal for use with aircrafts. Length 300 mm (12").



### KZLNS needlepoint coupler

Push on needlepoint grease extension, ideal for use with four wheel drive vehicles. Length 300 mm (12")



### KZSNR 90° needlepoint coupler

An 110 mm (4 1/4") needlepoint coupler with a 90° bend at the end.



### ZSB swivel

A 360° swivel supplied either separately or with the B2 Booster Gun. Threads 1/8" NPT (M) x 1/4" NPT (F).



## grease extension hoses

### KDE8 extension

A 200 mm (8") push on rigid extension coupler with a nipple to fit onto the KY coupler. For use with grease guns.



### KFR rigid/flexible extension

A 330 mm (13") extension with a sliding sleeve that allows for either flexible or rigid operation. The thread is 1/8" BSP (M) and fitted with a KY coupler.

